


MODEL: SD-15RDW-MIL




FEATURES



Size / Type
15"




Brightness
1000 (typ.)



Contrast
700: 1 (typ.)



Max. Colors
16.2 M



Viewing Angle
-80~80(H); -80~60(V);



Resolution
1024 x 768 @ 60Hz

SPECIFICATION

PANEL SPECIFICATION	
Size / Type	15"
Resolution	1024 x 768
Brightness	800 (typ.)
Contract Ratio	700 : 1 (typ.)
Max. Colors	16.2M Colors (8 bits/color)
Viewing Angle	-80~ 80 (H); -80~ 60 (V)
Touch Screen	5 - wire resistive touch screen
SYSTEM	
Brightness	0~100% Dimming Control
OSD Button	5 Buttons Front OSD Controller (Power On/Off, Menu, Up, Down, Reset)
Bonding	Optical bonding between panel and touch
Mounting	VESA Mount / Panel Mount
Material	Full Alu . alloy
Audio	Audio line In for optional
Coating	1. Bottom layer coating for EMI protection 2. Electronic parts coating for salt/fog protection
INPUT / OUTPUT	
HDMI	1 x HDMI Input (D38999 connector)
VGA	1 x VGA Input (D38999 connector)
Video Input	1 x Video , PAL/NTSC (Optional)
USB	1 x USB for touch screen (D38999)
Power Input	1 x DC 28V Input (D38999 connector)
HD-SDI	1 x HD - SDI (BNC or D38999)
OSD BUTTONS	
OSD Input	10 - Fn OSD programmable keys (Esc,Fn1,Fn2,No.1 - 5,Power On/Off, Up/Down/Space/Enter)
OSD Function	Color, Position, Auto - adjustment, Factory Settings

ENVIRONMENT TOLERANCE	
Operating Temperature	-20 deg. C to 60 deg. C
Storage Temperature	-32 deg. to 75 deg. C
Humidity	5 to 95% (Non Condensing)
MIL - STD - 810G	Vibration, Shock, Temperature Shock, Salt Fog, Atmosphere Pressure
MIL - STD - 461F	Compliance to CE102, RE102, CS101, CS104, CS116
IP Level	Full IP65

DIMENSIONS	
Dimensions	482(W) x 354(H)x 80(D)mm
Weight	9KG
VESA	100 x100 M6 VESA holes

DRAWINGS

